



Available features of the drop-in Air Screen Merchandiser.



VARIETY OF SIZES

A wide offering of sizes for drop-ins: 36", 48" and 60" lengths with a 42" height.

MAINTAINS TEMPERATURE

Meets NSF7 type 2 requirements with maintain 33°-41° temperature in 80° ambient environment with 55% relative humidity.

SHOWCASE

Designed to showcase all prepackaged products. Extra pan in the base of the display area is perfect for salads, sandwiches, wraps, fruit plates - virtually anything.

LARGE CAPACITY

Maximizes display space; three lighted glass display shelves are standard.

UPSCALE APPEARANCE

The glass display area allows for maximum visibility of the product.

REAR LOADING DOORS

Sliding locking doors provide easy access for loading product from the back - perfect for units built into a serving line.

AIR SCREEN DESIGN OFFERS DESIGN FLEXIBILITY

The open front not only puts product right in front of your customers but it is also great for speed of service and getting your customers through the line fast.

ADJUSTABLE SHELVES

Adjustable shelves offer flexibility of display. The shelves can be moved in 1" increments and tilted into three positions.

IN GOOD LIGHT

Fluorescent slim line lighting is hidden below each shelf and is standard on all models.

EASE OF SERVICEABILITY

Slide out condensing units allow for easy serviceability.

SECURITY COVER

Options for the drop-in air curtain merchandiser include a night security cover.



REACH-INS / PREP TABLES / SHELLEY® SERVING COUNTERS / DROP-INS / COMPONENT CRAFTED EQUIPMENT
PHONE: 800-733-8948 or +1 989-773-7981 / FAX: 800-669-0619 / WEB: WWW.DELFIELD.COM



DFASM 01/11

ASM SERIES - DROP-IN REFRIGERATED AIR SCREEN MERCHANDISER



ASM-48

Product Information

- All glass display area and top slim line fluorescent lighting showcases product
- Bottom shelf is a recessed pan, perfect for bottles or taller items
- Three 1" adjustable glass shelves with fluorescent lights standard
- Slide out condensing unit allows for easy serviceability
- R404A refrigerant
- Shelves can be positioned three ways: completely flat, slanted and full tilt
- Drain requires hard plumbing (unless condensate evaporator option is selected)
- Hinged rear doors make replenishment and loading easy
- Meets NSF Tier 2 requirements which maintains 33°F to 41°F temperature in 80°F environment with 55% relative humidity
- Standard with two louvers for proper airflow in base
- One year parts and labor standard warranty

Specifications and Prices

Model Number	Description	L	D	H	Cutout Dimension	H.P	V/Hz/Ph	Amps	NEMA Plug	Ship Weight	List price
ASM-36	36.25" L Drop-in air screen merchandiser	36.25	26.00	63.48	35.00" x 25.38"	1/2	115V/60Hz/1Ph	10.8	5-15P	350	\$22,575
ASM-48	48.25" L Drop-in air screen merchandiser	48.25	26.00	63.48	47.00" x 25.38"	3/4	115V/60Hz/1Ph	12.8	5-20P	457	\$23,880
ASM-60	60.25" L Drop-in air screen merchandiser	60.25	26.00	66.48	59.00" x 25.38"	1	115-208/230V/60Hz/1Ph	12.8	14-20P	593	\$26,053

Accessories	List Price
ASMNC-36 (not field-installable) Night Security Cover	\$2,348
ASMNC-48 (not field-installable) Night Security Cover.....	\$2,376
ASMNC-60 (not field-installable) Night Security Cover.....	\$3,093
ASMCE-36 (not field-installable) Condensate evaporator (Cord spec for ASM-36 w/ condensate evap: Nema 14-20P @ 115-208/230V-60C-1PH-10.8A).....	\$660
ASMCE-48 (not field-installable) Condensate evaporator (Cord spec for ASM-48 w/ condensate evap: Nema 14-20P @ 115-208/230V-60C-1PH-12.8A).....	\$660
ASMCE-60 (not field-installable) Condensate evaporator (Cord spec for ASM-60 w/ condensate evap: Nema 14-50P @ 115-208/230V-60C-1PH-26A).....	\$890
ASM220V220V/50Hz electrical system.....	\$932
ASML Laminated sides & top	\$799
ASMR Remote (specify refrigerant).....(CREDIT)	\$1,730

Additional Warranty	Net Pricing
One year parts and labor contract	\$246
Two year parts and labor contract	\$461
Five year compressor warranty	
1/2HP	\$122
3/4HP	\$128
1HP.....	\$169



Effective August 2009. All prices F.O.B. Mt. Pleasant, Michigan 48858. Prices may vary on accessories ordered from the Parts Department. Visit www.delfield.com for specification sheets.